

# ENERGY STAR® Power and Performance Data Sheet

Dell PowerEdge R710 Featuring the Dell Energy Smart 870W PSU and Intel Xeon E5620



## System Characteristics

Form Factor	2U
Available Processor Sockets	2
Available DIMM Slots / Max Memory Capacity	18/192 GB
ECC and/or Fully Buffered DIMMs	Yes
Available Expansion Slots	4 PCI-E
Minimum and Maximum # of Hard Drives	0 to 8
Redundant Power Supply Capable?	Yes
Power Supply Make and Model	Dell 870W
Power Supply Output Rating* (watts)	870
Minimum and Maximum # of Power Supplies	1 or 2
Input Power Range (AC or DC)	100-240VAC
Power Supply Efficiency at Specified Loadings*	77.7%@10%, 87.1%@20%, 91.5%@50%, 91.05%@100%
Power Supply Power Factor at Specified Loadings*	0.71@10%, 0.87@20%, 0.97@50%, 0.99@100%
Operating Systems Supported	Microsoft Windows® Server 2003 and 2008 Microsoft Windows Essential Business Server 2008 Microsoft Windows Small Business Server 2008 Red Hat Enterprise Linux 4 and 5 Citrix XenServer 5.x <sup>3</sup> Vmware ESXi 3.5 <sup>3</sup> SUSE Linux Enterprise Server 10 and 11
Installed Operating System for Testing	Microsoft Windows Server 2003

\* Note: Power supply information is for a single power supply only

## System Configurations

Processor Information	2x Intel Xeon E5620
Memory Information	6x UDIMMs, 2 GB, 1333MHz
Internal Storage	4x 146GB 10k SAS HDDs
I/O Devices	4x 1Gb LOMs + 2x dual port 1 Gb NICs
Power Supply Number and Redundancy Configuration	2, 1+1 Redundant
Management Controller or Service Processor Installed?	Yes
Other Hardware Features / Accessories	iDRAC6 Enterprise, PERC6/I, ODD

## Power Data

Idle Category (1S and 2S only)	Category D: Managed Dual Installed Processor (2P) Servers
ENERGY STAR Idle Power Allowance (1S and 2S only)	218
Measured Idle Power (watts)	128.7
Power at Full Load* (watts)	247.8
Benchmark / Method Used for Full Load Test	Sandra Dhrystone isse 4.2
Test Voltage and Frequency for Idle and Full Load Test	115 V/60 Hz
Range of Total Estimated Energy Usage ** (kWh/year)	2,254 to 4,341
Link to Detailed Power Calculator (if available)	<a href="http://WWW.Dell.com/CALC">WWW.Dell.com/CALC</a>

\* Note: Full load power represents the sustained, average power at 100% load of the given workload, and does not necessarily represent the absolute peak power or the highest average, sustained power possible for other workloads.

\*\* Note: Estimated kWh/year gives the absolute range of energy use a user could expect from continuous operation (24x7x365) and ranges from 100% idle usage to 100% full load operation. The calculation also includes typical data center overhead at a ratio of 1 watt of overhead to every 1 watt of IT load (corresponding to a PUE of 2.0). Closer approximations may be found by using established power calculators and specific information about the intended operating environment (e.g., average time at idle, data center PUE, etc.).

## Power and Performance for Benchmark #1

Benchmark #1	Benchmark Used and Type of Workload	Sandra Dhrystone isse 4.2
	Avg. Power Measured During Benchmark Run	252.2
	Benchmark Performance Score	148
	Power Performance Ratio (perf score/avg. power)	0.59
	Link to Full Benchmark Report (Where Available)	

## Power and Performance for Benchmark #2 (optional)

Benchmark #2	Benchmark Used and Type of Workload	
	Avg. Power Measured During Benchmark Run	
	Benchmark Performance Score	
	Power Performance Ratio (perf score/avg. power)	
	Link to Full Benchmark Report (Where Available)	

# ENERGY STAR Power and Performance Data Sheet

Dell PowerEdge R710 Featuring the Dell Energy Smart 870W PSU and Intel Xeon E5620  
Page 2 of 2



<b>Power Saving Features</b>	<b>Enabled on Shipment</b>	<b>End-User Enabling Required</b>
Processor Dynamic Voltage and Frequency Scaling	YES	NO
Processor or Core Reduced Power States	YES	NO
Power Capping	YES	NO
Variable Speed Fan Control Based on Power or Thermal Readings	YES	NO
Low Power Memory States	YES	NO
Low Power I/O States	YES	NO
Liquid Cooling Capability	NO	N/A
Other1:		
Other2:		
Other3:		
Other4:		

## Power and Temperature Measurement and Reporting

Input Power Available & Accuracy?	Yes, +/- 5% for 20%-100% of max PSU load
Input Air Temp Available & Accuracy?	Yes, +/- 2%
Processor Utilization Available?	Yes
Other Data Measurements Available & Accuracy?	
Compatible Protocols for Data Collection	IPMI
Averaging method and time period	Power: 1 min running average of 2s interval samples. Temperature: no

## Thermal Information \*

	<b>Minimum</b>	<b>Typical</b>	<b>Maximum</b>
Reference Configurations	1, Intel Xeon E5504 1 UDIMM, 1GB, 1067MHz 1 146GB 10k SAS HDD 4x 1Gb LOMs iDRAC 6 Express SAS 6iR	2, Intel Xeon E5540 6 RDIMM, 2GB, 1067MHz 6 146GB 10k SAS HDD 4x 1Gb LOMs 2x Dual port 1Gb NICs iDRAC 6 Enterprise PERC 6i, ODD	2, Intel Xeon X5570 12 RDIMM, 16GB, 1067MHz 8 146GB 10k SAS HDD 4x 1Gb LOMs 4x Dual port 1Gb NICs iDRAC 6 Enterprise PERC 6i, ODD
Total Power Dissipation (watts)	147.0	299.0	518.0
Delta Temperature at Exhaust at Peak Temp. (°C)	6.6 (11.4 at nominal temp)	10.7 (19.3 at nominal temp)	16.9 (21.6 at nominal temp)
Airflow at Maximum Fan Speed (CFM) at Peak Temp.	40 (1 cpu/4 fan when iDRAC-managed, else 108)	50 (2 cpu/5 fan when iDRAC-managed, else 135)	55 (2 cpu/5 fan when iDRAC-managed, else 135)
Airflow at Nominal Fan Speed (CFM) at Nominal Temp.	23	28	43

\* Thermal information is provided for the minimum, typical and maximum configurations for the model line  
References: ASHRAE Extended Environmental Envelope Final August 1, 2008  
Thermal Guidelines for Data Processing Environments, ASHRAE, 2004, ISBN 1-931862-43-5  
Peak temperature is defined as 35 °C, Nominal Temperature is defined as 18 - 27 °C

## Notes

1. SPECpower\_ssj2008 is a registered trademark of the Standard Performance Evaluation Corporation (SPEC). Benchmark results stated above reflect results published on XXX/XX. For the latest SPECpower\_ssj2008 benchmark results, visit [http://www.spec.org/power\\_ssj2008](http://www.spec.org/power_ssj2008).