

# DELL POWEREDGE R410 SERVER



The Dell™ PowerEdge™ R410 is a powerful and ultra-dense 2-socket 1U server that offers the performance of Intel® Xeon® 5500 and 5600 series processors, DDR3 memory, the availability of up to four hard drives (3.5” or 2.5”), and an exceptional value.

The PowerEdge R410 features include an available “open” HPCC (High Performance Computing Cluster) software stack, excellent diagnostics with an interactive LCD, and an optimum chassis depth of 24” for space-constrained data centers and HPCC environments.

The PowerEdge R410 was developed with a purposeful design—energy-optimized technology, advanced virtualization capabilities, and simplified systems management.

## **PURPOSEFUL DESIGN**

The PowerEdge R410 takes advantage of Dell’s outstanding system commonality and reliability. Quick-release rack latching and purposeful placement of interface ports and power supplies enable easy installation and redeployment. Robust metal hard drive carriers and an all steel control arm can further increase structural integrity.

The purposeful design of the PowerEdge R410 provides reduced complexity, showcasing clutter-free cable routing for more efficient airflow and easier maintenance. An LCD screen positioned by the front of the bezel provides aisle-level access to deploy the server.

## **ENERGY-OPTIMIZED TECHNOLOGY**

The PowerEdge R410 features energy-tuned technologies that reduce power consumption while increasing performance capacity so you can compute more while consuming less. The energy-efficient power supply units are right-sized for system requirements, with improved system-level design efficiency, policy-driven power and thermal management, and highly efficient standards-based Energy Smart components. A robust fan cage design with hot-plug, single-pull fan modules provides efficient airflow and eases maintenance. Energy efficient and compact, the PowerEdge R410 is designed with value and reliability for HPCC computing environments.

## **SIMPLIFIED SYSTEMS MANAGEMENT**

The next-generation of Dell OpenManage™ suite of management tools is designed to provide efficient operations and standards-based commands that integrate with existing systems for effective control.

Dell Management Console (DMC) powered by Altiris™ from Symantec™ helps simplify operations and create stability by shrinking infrastructure management to one console. This console delivers a single view and a common data source into the entire infrastructure management. DMC has an easily extensible, modular foundation that can provide basic hardware management or more advanced functions, such as asset and security management. Dell Management Console is designed to reduce or eliminate manual processes, enabling you to save time and money for more strategic technology usage.

Secure and efficient, the Dell Lifecycle Controller delivers integrated manageability through a single access point. The Unified Server Configurator (USC) interface enables easy access to the tool which is embedded and integrated into the system for significant flexibility and capability. The Lifecycle Controller is an integrated interface for deploying operating systems with built-in driver installations, BIOS and firmware update and rollback, hardware configuration, and diagnostics.

## **ABOUT DELL GLOBAL SERVICES**

Dell Services can help reduce IT complexity, lower costs, and eliminate inefficiencies by making IT and business solutions work harder for you. The Dell Services team takes a holistic view of your needs and designs solutions for your environment and business objectives while leveraging proven delivery methods, local talent, and in-depth domain knowledge for the lowest TCO.

| Feature                                 | DELL™ POWEREDGE™ R410  |  |
|---|--|--|
| <b>Form Factor</b>                      | 1U   |  |
| <b>Processors</b>                       | Latest quad-core or six-Core Intel® Xeon® 5500 and 5600 series processors  |  |
| <b>Processor Sockets</b>                | 2  |  |
| <b>Front Side Bus or HyperTransport</b> | Intel® QuickPath Interconnect (QPI)  |  |
| <b>L2/L3 Cache</b>                      | 4MB and 8MB  |  |
| <b>Chipset</b>                          | Intel 5500 Chipset   |  |
| <b>Memory</b>                           | Up to 64GB (8 DIMM slots): 1GB/2GB/4GB/8GB DDR3 800MHz, 1066MHz or 1333MHz<br>16GB Quad-Ranked 1066MHz DIMMs   |  |
| <b>I/O Slots</b>                        | 1 PCIe x 16 (True x16, Gen2), 1 Proprietary for SAS 6/iR Modular card only   |  |
| <b>Drive Controller</b>                 | Chipset based SATA, SAS 5/E, LSI2032 (for tape only)   |  |
| <b>RAID Controller</b>                  | <b>Internal:</b><br>PERC H200 (6Gb/s)<br>PERC H700 (6Gb/s) with 512MB Non-Volatile cache<br>PERC H700 (6Gb/s) with 512MB battery-backed cache<br>SAS 6/iR<br>PERC 6/i with 256MB battery-backed cache<br>PERC S100 (software based)<br>PERC S300 (software based)  | <b>External:</b><br>PERC H800 (6Gb/s) with 512MB Non-Volatile cache<br>PERC H800 (6Gb/s) with 512MB of battery-backed cache<br>PERC 6/E with 256MB or 512MB of battery-backed cache<br><b>External HBAs (non-RAID):</b><br>6Gbps SAS HBA<br>SAS 5/E HBA<br>LSI2032 PCIe SCSI HBA |
| <b>Drive Bays</b>                       | 4x 3.5" Cabled Hard Drive<br>Or 4 x 3.5" Hot-swap Hard Drive<br>Or 4x 2.5" Hot-swap hard Drive<br>And one slim type drive bay for DVD-ROM or DVD+/-RW  |  |
| <b>Maximum Internal Storage</b>         | Up to 4 TB SATA or Near Line SAS   |  |
| <b>Hard Drives<sup>1</sup></b>          | 3.5" SATA ( 7.2K rpm) 160GB, 250GB, 500GB, 750GB, 1000GB<br>3.5" Near Line SAS ( 7.2K rpm) 500GB, 750GB, 1000GB<br>3.5" SAS (15K rpm) 146GB, 300GB, 450GB<br>3.5" SAS (10K rpm) 600GB<br>3.5" 2.0TB SATA<br>2.5" SAS (10K rpm) 73GB, 146GB, 300GB<br>2.5" SATA SSD 25GB, 50GB, 100GB   |  |
| <b>Tape Support</b>                     | All External: RD1000, DAT-72, LTO2-L, LTO3-060, LTO4-120, full-height versions also available.   |  |
| <b>Network Interface Cards</b>          | Embedded Dual-port Broadcom® NetXtreme™ II 5716 Gigabit Ethernet<br>Intel® Gigabit ET Dual Port Server Adapter and Intel® Gigabit ET Quad Port Server Adapter<br>Intel® 10GbE NIC<br>Intel® Single Port 1GbE NIC<br>Intel® Dual Port 1GbE NIC<br>Intel® Quad Port 1GbE NIC<br>Broadcom® 10GbE NIC<br>Broadcom® Dual Port 1GbE NIC  |  |
| <b>Power Supply</b>                     | Non-Redundant, 480W (80+ BRONZE)<br>Optional Redundant, 500W (80+ GOLD)  |  |
| <b>Availability</b>                     | Quad-pack LED Diagnostic or LCD diagnostic with hot-swap HDD chassis; TPM; optional hot-swap hard drives; optional hot-swap redundant power supply; optional PERC 6/i RAID controller with battery-backed cache; toolless hot-swap hard drive chassis  |  |
| <b>Video</b>                            | Integrated Matrox® G200  |  |
| <b>Remote Management</b>                | BMC, IPMI2.0 compliant<br>Optional iDRAC6 Enterprise, iDRAC6 Express   |  |
| <b>Systems Management</b>               | Dell™ OpenManage™  |  |
| <b>Rack Support</b>                     | 1U Rack  |  |
| <b>Operating Systems</b>                | Microsoft® Windows® Small Business Server 2008<br>Microsoft® Windows® Essential Business Server 2008<br>Microsoft® Windows® Server® 2008 SP2, x86/x64 (x64 includes Hyper-V™)<br>Microsoft® Windows® Server® 2008 R2, x64 (includes Hyper-V™ v2)<br>Microsoft® Windows® HPC Server 2008<br>Novell® SUSE® Linux® Enterprise Server<br>Red Hat® Enterprise Linux®<br><br>For more information on the specific versions and additions, visit <a href="http://www.dell.com/OSsupport">www.dell.com/OSsupport</a> . |  |

<sup>1</sup> For hard drives, GB means 1 billion bytes and TB equals 1 trillion bytes; actual capacity varies with preloaded material and operating environment and will be less.

## SIMPLIFY YOUR SERVERS AT [DELL.COM/POWEREDGE](http://DELL.COM/POWEREDGE)

Copyright Dell 2010. All rights reserved. Dell, the DELL logo, the DELL badge, PowerEdge, and OpenManage are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind.

